

SELF LEVELING

Unique self-levelling design offers slope correction up to 10.5%

EASY ASSEMBLY

Simple design ensures rapid installation

HEAVY DUTY

Ultimate compression strength for maximum durability

VERSITILE

For use with any type of calibrated paving - concrete, granite, porcelain, etc.



Size Range

The vast height range of these adjustable pedestal allows it to overcome very large changes in surface level, and also conceal services, ductwork and pipes beneath the paving.



1.6 - 2.2 in 2 - 2.75 in 2.75 - 4.3 in 4.3 - 6.3 in 5.9 - 8.3 in 7.9 - 11.8 in 11.8 - 15.7 in 15.7 - 19.7 in 19.7 - 23.6 in 23.6 - 27.5 in 27.5 - 31.5 in 31.5 - 35.4 in 35.4 - 39.4 in
40 - 56mm 50 - 70mm 70 - 110mm 110 - 160mm 150 - 210mm 200 - 300mm 300 - 400mm 400 - 500mm 500 - 600mm 600 - 700mm 700 - 800mm 800 - 900mm 900 - 1000mm

Self-Levelling Paving Support Head

Fastest installation time of any pedestal system available due to its innovative self-levelling head design.

Adjustable Threaded Section

This heavy grade threaded section allows you to adjust the height in minute increments, within the given range. It's easy to adjust, simply grab and twist.

Height Extension Collar

A very simple design with a single 'click' motion to attach, these extension collars build up the pedestals in 4-inch (100mm) increments.

Wide Supporting Base

Creates an evenly spread load on the surface below, ensuring that membranes are well protected. Pedestals are loose laid and do not require fixing to the floor. Designed with water drainage holes to prevent moisture build-up.